

SB7560S 75A SCR


FEATURES

- High thermal cycling performance
- High voltage capacity
- Very high current surge capability

APPLICATIONS

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Parameters Summary



ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T _{STG}	-40 ~ 150	°C
Operating junction temperature range	T _J	-10 ~ 125	°C
Repetitive peak off-state voltage (T = 25°C)	V _{DRM}	1200 / 1000	V
Repetitive peak reverse voltage (T = 25°C)	V _{KRM}	1200 / 1100	V
Non repetitive surge peak Off-state voltage	V _{DSSM}	V _{DRM} + 100	V
Non repetitive peak reverse voltage	V _{DRM,NR}	V _{DSSM,NR} + 100	V
RMS on-state current (T = 100°C)	I _{T(RMS)}	75	A
Non repetitive surge peak on-state current	I _{TSM}	700	A
I ² t value for fusing (tp=10ms)	I ² t	2450	A·ms
Critical rate of rise of on-state current (I = 2×IGT, tr ≤ 100 ns)	di/dt	150	A/μS
Peak gate current	I _{GM}	5	A
Average gate power dissipation	P _{G(AV)}	2	W

Thermal Resistances

Symbol	Parameter	Value	Unit
R _{th(j-c)}	Junction to case (DC)	TO-3P	0.60
		TO-247	0.55
			°C/W


ELECTRICAL CHARACTERISTICS ($T=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Test Condition	Parameter	Min	Max	Unit
$I_{G,T}$	$V_D = 12\text{V} R = 140\Omega$	I_G	0	10	μA
$V_{G,GT}$		$V_{G,GT}$	-1	1	V
$V_{GD,SD}$	$V_D = 12\text{V} R = 1\text{k}\Omega$	$V_{GD,SD}$	-12	12	V
I_L	$I_T = 12\text{A}$	I_L	0	12	A
I_T	$V_D = 12\text{V} R = 1\text{k}\Omega$	I_T	0	140	A
$\alpha \sqrt{f_{T1}}$	$V_D = 12\text{V} R = 1\text{k}\Omega$	$\alpha \sqrt{f_{T1}}$	0.001	0.002	$\text{ms}^{-1/2}$


STATIC CHARACTERISTICS

Symbol	Parameter	Value	Unit
V_{BR}	$ITM = 140\text{A} tp = 380\mu\text{s}$	1200	V
V_{BR}	$V_D = V_N = V_M = V_S$	1600	V
V_{BR}	$V_D = V_N = V_M = V_S$	1000	V
V_{BR}	$V_D = V_N = V_M = V_S$	1200	V


Ordering Information Scheme



TO-247 Package Mechanical Data



TO-3P Package Mechanical Data



Ref.	Dimensions				
	Millimeters		Inches		
	t_{viaMin}	t_{viaMax}	t_{viaMin}	t_{viaMax}	t_{viaMin}
A	4.40		4.60	0.173	0.181
B	1.40		1.60	0.055	0.062
C	15.48		15.88	0.609	0.625
D	0.50		0.70	0.019	0.027
E	2.70		2.90	0.106	0.114
F	15.92		16.32	0.626	0.642
G	20.27		20.67	0.798	0.817
H	15.15		15.35	0.590	0.604
J		5.45			0.214
K	1.10		1.30	0.043	0.051
L	1.15		1.35	0.045	0.053
P	2.68		3.08	0.105	0.121
R		4.20			0.165

FIG.1 Maximum power dissipation versus on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of $I_2 t$ ($dI/dt < 50\text{A}/\mu\text{s}$)




FIG.2: on-state current versus case temperature




FIG.4: On-state characteristic curves (maximum values)




FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature

